




## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification <sup>6</sup> :</b> <b>E21B 17/08, 43/10, 43/08, F16L 13/14</b>	<b>A1</b>	<b>(11) International Publication Number:</b> <b>WO 98/42947</b> <b>(43) International Publication Date:</b> 1 October 1998 (01.10.98)
<b>(21) International Application Number:</b> PCT/GB98/00863 <b>(22) International Filing Date:</b> 20 March 1998 (20.03.98)  <b>(30) Priority Data:</b> 9705928.1           21 March 1997 (21.03.97)   GB 9723338.1           4 November 1997 (04.11.97)   GB  <b>(71) Applicant (for all designated States except US):</b> PETROLINE WELLSYSTEMS LIMITED [GB/GB]; Offshore Technol- ogy Park, Claymore Drive, Bridge of Don, Aberdeen AB23 8GD (GB).  <b>(72) Inventor; and</b> <b>(75) Inventor/Applicant (for US only):</b> METCALFE, Paul, David [GB/GB]; North Wing, Bucklerburn Steading, Peterculter AB14 0NP (GB).  <b>(74) Agents:</b> McCALLUM, William, Potter et al.; Cruikshank & Fairweather, 19 Royal Exchange Square, Glasgow G1 3AE (GB).		<b>(81) Designated States:</b> AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, GW, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).  <b>Published</b> <i>With international search report.</i> <i>Before the expiration of the time limit for amending the</i> <i>claims and to be republished in the event of the receipt of</i> <i>amendments.</i>

**(54) Title:** EXPANDABLE SLOTTED TUBING STRING AND METHOD FOR CONNECTING SUCH A TUBING STRING

**(57) Abstract**

An expandable tubing assembly comprises a tubular connector (16) defining overlapping longitudinal slots (18), the connector (16) comprising end portions (20, 21) and an intermediate portion (22). The slots (18) extend over the whole length of the connector (16), but the only slot overlap occurs in the intermediate portion (22). The assembly further comprises lengths of expandable tubing (24, 25) defining overlapping longitudinal slots (12) and having end portions defining nodes (38) between and beyond the ends of the tubing slots (12). Tubing threads (28, 29) are formed on the end most tubing nodes. The connector end portions define threads (26, 27) and are coupled with the threads (28, 29) formed on the nodes of the respective end portions of the tubing lengths.